




Tender Ref. No: RGMCET/AICTE IDEA LABS / 2025-26(1).

Date: 21.01.2026


### **Tender Notice**

Sealed/Online tenders are invited from reputed and experienced suppliers, manufacturers, or authorized distributors for the **supply, installation, and commissioning of equipment, tools, and machines** for setting up an **AICTE IDEA Lab** at our institute. The laboratory is to be developed as per the AICTE guidelines for promoting innovation, design thinking, and prototyping skills among students and faculty. The detailed specifications of the required items are enclosed with this document.

<b>S. No</b>	<b>Equipment</b>	<b>Preferred brands if any</b>	<b>Specifications</b>	<b>Qty</b>
1	Single Nozzle 3D printer	Branded Company Product with at least three years product warranty	Printing Technology: Fused Filament Fabrication (FFF) or Fused Deposition Modeling (FDM). Printable Area: The minimum printable area should be at least 310 x 310 x 310 mm or above Printer Design: Core XY or Cartesian. Temperature Range: Hot end: Up to 300°C or above bed: Up to 120°C. or above. Nozzle: Compatible with All polymers, 0.4, 0.6 and 0.8mm Steel Sheet: Provided with satin or smooth PEI surface. Filament Diameter: 1.75mm (supports PLA, PETG, ASA, ABS, etc.). Extruder: Gearbox with 1/10 ratio, Speed : 550 MM/Sec or above Stepper Drivers for smooth motion. or equivalent Stepper Motors: Choose between 1.8° or precise 0.9° X, Y stepper motors. LCD Screen: 3.5" graphic 65k color screen or larger. Connectivity: USB drive, LAN, or internet. Supported Materials: PLA, PETG, ASA, ABS, PP, PC, flexible filaments, and more. Wi-Fi Module: Built-in (network connectivity not required for setup or operation). Compatibility: Windows, macOS, Linux. Dimensions: The maximum physical dimensions of the system 700 X 700 X 700 or above. Fully enclosed Machine.	1
2	PCB Milling Machine	Branded Company	Cuttable Materials: Modeling Wax, Chemical Wood, Foam, Acrylic, Poly Acetate, ABS, PCB, Copper clad, etc	1




		Product with at least three years product warranty	Table Size: 225 (X) × 150 (Y) mm or more  Drive System: Stepping Motor (X, Y, Z Axis) Operating Speed: 800 mm/min Software Resolution: 0.01 mm/step Position accuracy: 0.01 to 0.02 mm Max Travel Speed (mm/sec)-58 (2.28 ") Drilling (mm)-0.2 -3.175 (8-125 mil) Maximum Drilling Cycles/ Min-50  Spindle Motor: DC Motor Type 380 or More Spindle Speed: Adjustable 20,000 and above rpm or more Tool Chuck Type: Collet Interface: USB or cable Control Commands: RML-1, NC code Power Supply: DC 24V, 2.5A (via AC 100-240V, 50/60Hz adapter) Power Consumption: Approx. 50 W or more	
3	CO <sub>2</sub> Laser Cutting Machine	Branded Company Product with at least three years product warranty	Working Area: Min 600 x 900 mm or above Laser Type: CO <sub>2</sub> DC Glass Laser Tube/RF Metal Laser Tube Laser Power: 80/100W Wave Length: Upto 10.6 Micrometer Cutting Speed: 30000 mm/min or more Engraving Speed: 64000 mm/min or more XY Axis: LM Guide Rail or equivalent Cooling: Air/ Water Cooling Supply Voltage: 230V/415 V Accessories: CO <sub>2</sub> Focus Lens: 1 No. Mirror 25mm: 3 Nos. Acetone: 1 litre Acrylic sheet: 2 Nos	1
4	Vinyl Printer	Branded Company Product with at least Two years Warranty	Dimensions: 50 cm x 15 cm x 15 cm or above Weight: 15.4 lbs or less Max cut size using machine mat: 11.5 inch x 23.5 inch or more Cut speed: up to 14.1 ips	1
5	3D Scanner	Branded Company Product with at least three years product warranty	Technology: Stereo camera structured light with focusable cameras or equivalent CPU: Quad-core 64-bit SoC, 1.5GHz with integrated GPU RAM: 4 GB Projector: DLP MEMS mirror or equivalent Camera Sensor: Sony 13 MP or better Scan Speed: 4 seconds or more Working Distance : Effective Working Distance: 160mm-1400mm Scan Speed : 980,000points/s, up to 14FPS Align Modes : Feature Alignment, Hybrid	1



			Alignment, Texture Alignment, Global Markers Safety : Eye-safe Texture Scan : Yes Interface : USB2.0 or above Outdoor Scanning : Yes Output Formats : OBJ; STL; PLY; P3; 3MF  Scanning Environment: Indoor and outdoor (shaded) Texture / Color Scanning: Yes Minimum Capturable Feature Size: 0.2 mm or less  Scanner Weight: 500 grams or less Scanner Dimensions: upto 240 × 60 × 60 mm Compatible OS: Any OS supporting a modern web browser	
6	Lathe Machine cum milling	Branded Company Product with at least three years product warranty	Centre Width: Up to 400 mm or better Height of Centers: Up to 88 mm Maximum Workpiece Diameter: Up to 100 mm Machine Base: Cross-ribbed surface, highquality cast iron with ground prismatic guide, capable of fitting milling/drilling attachment Spindle: Supported with adjustable taper roller bearings Spindle Receiver: MK3 or compatible Spindle Drill Hole: Up to 22 mm or better Spindle Concentricity: Up to 5 microns or better Chuck: 3-jaw chuck as per DIN 6386, centrically clamped, 100 mm diameter or better Run Out (without Chuck): Up to 10 microns Sleeve Receiver: MK2, retractable sleeve with scale Spindle Speed Range: Between 50 to 2500 rpm Speed Stages: 6-8 Motor Rating: 550W or better, induction motor, single phase 230V Traverse Cross: Up to 70 mm or better Traverse Longitudinal: Up to 300 mm or better Weight (Complete): Up to 55 kg or more  Additional Accessories: Splash guard and chip collecting tray: 1 No. Cutter set with tungsten inserts: 2 Nos. Milling Attachment: 1 nos Tungsten disposable tips ten-piece set: 1 No. Sample workpieces (Nylon Rod, Aluminium Rod) Desktop: 1 No.	1
7	CNC Router	Branded Company	Working Area: Min 1300 x 2500 mm Z Axis Working Area: 200 or above	1



		Product with at least three years product warranty	Resolution: $\pm 0.03/300\text{mm}$ or more CNC Spindle: 3KW or more Lathe Structure : Welding Steel Structure or equivalent XYZ Structure: Rack Pinion , Ball Screw Linear Rails Max Spindle Speed : Min 18000RPM Table: T-Slot/Vacuum Bed/Water Bed Repeatability: $\pm 0.03$ Working Mode: Stepper Motor/Servo Motor Dust Collector : To be included by Vendor Voltage: AC 220V/415V, 50/60 Hz, 3 Phase	
8	Belt and Disc Sanding Machine	Branded Company Product with at least three years product warranty	Motor: 230V 50Hz Power: 380W S2 30min No-load Speed: 1450rpm or more Belt Size: 100x914mm or less Disc Size: 150mm or better Table Titing Range: 0°-45° Belt Titing Range: 0°-90° Table Size: upto 190x125mm	1
9	Scroll Saw	Branded Company Product with at least three years product warranty	Power input: 50 Watt Thickness of Cut: 50 mm (2 inch) Throat: 406 mm (16 inch) Length of Stroke: 18 mm (11/16 inch) Strokes Per Minute: 400-1,600 SPM Overall Length: 600 mm (23-5/8 inch)	1
10	Wood Turning Lathe	Branded Company Product with at least three years product warranty	Motor: 230V~50Hz, 550W, S2:15min or above Max. Disc Diameter: min 75 mm Max. Cutting Length: 450 mm or more Spindle Speed: 5 speeds such as 1600 / 2600 / 3200 RPM etc Material: Cast Iron Bed Height: 0.2 m Cable Length: 0.850 m	1
11	Bench Top Drill Machine	Branded Company Product with at least Three to Five years Warranty	Continuous rating input: Max. 250 W Capacity: Steel: Min 13 mm (1/2") Wood: Min 24 mm (15/16") No Load Speed (RPM): 570, 890, 1,300, 1,900, 2,670(50 Hz), 690, 1,070, 1,560, 2,280, 3,200(60 Hz) Net weight: Max. 20 kg (44.1 lbs.) Power supply cord: 1.75 m (5.7 ft) Additional Accessories: Bench Vise: 1 No., Drill Bit Set 10 Pcs: 1 No	1
12	Portable Welding Machine	Branded Company Product with at least Three to Five years Warranty	Welding Current (at 40°C, 10 min cycle): 120A @ 100%, 150A @ 60%, 200A @ 35% Supply Voltage: 240V +10%, -15%, 1 Phase, 50/60 Hz Open Circuit Voltage: 55V DC $\pm 5\text{V}$ Welding Current Range: 15-200 Amps DC Insulation Class: F Type	1




			Ingress Protection: IP21 Dimensions (L×W×H) with Handle: upto 320×120×195 mm Weight (Approx.): 4.3 kg or less	
13	Computerized Sewing Machine	Branded Company Product with at least three years product warranty	Motor: 120 W Max Sewing Speed: 860 SPM Power: 220 - 240 V Automation Grade: Automatic Max Stitch Length: 4mm Thread Type: Computerized Weight: 7.6 kg Number of Stitches: 120 Size/Dimension: 50.8 cm x 29.464 cm x 40.64 cm Maximum Stitch Width: 7 mm Number of Buttonhole Styles: 7 LCD Screen Display: Yes Bed Type Free Arm/Flatbed convertible Bobbin Type Drop & Sew Bobbin System	1
14	Filament Dehydrator	Branded Company Product with at least three years product warranty	Operating Temperature Range: Min 45°C-70°C Drying Time Setting: 0-48 hours or higher Hot-Air Heating: upto 360° circulation Moving Speed: 300 mm/s or more Power Rating: 160 W Shipping Weight: 2.5 kg	1
15	Reflow Oven	Branded Company Product with at least three years product warranty	No. of Waves: 7 or higher Heating Type: Infrared IC Heater Max. PCB Width: 300×320 mm or more Power Supply: AC 220V / 50Hz Peak Power: 1500W Cycle Time: 1-8 min or less Temperature Range: 0°C-280°C Overall Dimensions: min 350×450 mm Machine Weight: upto 25 kg	1
16	Digital multimeter	Branded Company Product with at least three years product warranty	Display Count: Up to 4000 DC Voltage Range: Up to 1000 V AC Voltage Range: Up to 1000 V DC Voltage Accuracy: ±0.5% or ±3 digits, whichever is higher AC Voltage Accuracy: Within ±1% + 3 digits DC Current Measurement: Up to 10 A AC Current Measurement: Maximum 10 A DC Current Accuracy: ±1.5% + 3 digits (approximate) AC Current Accuracy: ±1.5% + 3 digits (typical) Resistance Measurement: Up to 40 MΩ	5

			Resistance Accuracy: Estimated at $\pm 1.5\% + 3$ digits Capacitance Measurement: Up to 1000 $\mu\text{F}$ Capacitance Accuracy: $\pm 5\%$ or $\pm 5$ digits Operating Temperature Range: From 0°C up to approximately 40°C Storage Temperature Range: Between -30°C and 60°C Overall Dimensions (H×W×L): Approximately 183×91×49.5 mm Unit Weight: Around 455 grams Safety Compliance: As per IEC 61010-1 & IEC 61010-2-030 standards, suitable for CAT III 600V and CAT II 1000V environments with Pollution Degree 2 classification	
17	MSO 100 MHz	Branded Company Product with at least three years product warranty	Bandwidth: Up to 100 MHz Analog Channels: 4 or more Real-Time Sampling Rate: Maximum 1 GSa/s per channel Memory Depth: 10 Mpts per channel Waveform Update Rate: Approximately 120,000 wfms/s Vertical Resolution: 8 bits Vertical Scale: Ranging from 1 mV/div to 10 V/div Horizontal Scale: Spanning 1 ns/div to 100 s/div Spectrum Analyzer Frequency Range: DC to 500 MHz FFT Points: Up to 1M points for enhanced frequency domain resolution, Waveform Math Functions: Includes addition, subtraction, multiplication, division, minimum, maximum, root, square, absolute, inverse, derivative, integral, and low-pass filter Trigger Types: Edge, Pulse Width, Video, Pulse Runt, Rise & Fall (slope), Alternate, Timeout, Event-Delay, Time-Delay, and Bus Arbitrary Waveform Generator (AWG): Dualchannel, 25 MHz, supporting various waveforms such as sine, square, pulse, ramp, DC, noise, sinc, Gaussian, Lorentz, exponential rise/fall, haversine, and cardiac AWG Sample Rate: 200 MSa/s AWG Vertical Resolution: 14 bits Display: 8-inch WVGA TFT LCD (800 × 480 pixels) Data Logging Capability: Up to 1000 hours Segmented Memory: Supports up to 29,000 segments for efficient waveform storage and retrieval Connectivity: USB 2.0 (host and device),	1



			Ethernet (RJ45), and Go-NoGo BNC Dimensions (W × H × D): 380× 200× 125 mm or above Weight: 2 Kgs or above Safety Compliance: Conforms to IEC 61010-1 and IEC 61010-2-030 standards, suitable for CAT III 600V and CAT II 1000V environments with Pollution Degree 2 classification	
18	Digital oscilloscope	Branded Company Product with at least three years product warranty	<p>Number of Channels: Up to 2 independent analog inputs</p> <p>Memory Record Length: Up to 10 Mpts for extended waveform capture</p> <p>Bandwidth Limiting: Selectable 20 MHz bandwidth filter</p> <p>Sampling Rate: Maximum of 1 GSa/s real-time equivalent per channel</p> <p>Rise Time: <math>\leq</math> 3.5 ns depending on probe and settings</p> <p>Display: 7" TFT color LCD with 800×480 resolution</p> <p>Time Base Range: From 5 ns/div to 100 s/div, user-adjustable</p> <p>Vertical Resolution: 8-bit digital resolution</p> <p>Trigger Modes: Automatic, Normal, and Signal-dependent triggering</p> <p>Maximum Input Voltage: 300 Vrms (within safety limits)</p> <p>Input Sensitivity: Within the range of 1 mV/div to 10 V/div</p> <p>Input Coupling Options: Selectable among AC, DC, and Ground</p> <p>Trigger Coupling Modes: Configurable as AC, DC, High-pass, or Low-pass</p> <p>Physical Dimensions: Approximately 350 × 200 × 120 mm or above</p> <p>Unit Weight: 2.5 kg or above</p> <p>Input Impedance: Nominal <math>1 M\Omega // 16 pF</math></p> <p>Measurement Capabilities: Equipped for automatic parameter extraction, background noise filtering, and AUTOSET configuration for display scaling (time base/gain) Protocol Decoding Support: Capable of analyzing I2C, SPI, UART, CAN, and LIN communication protocols</p> <p>Standard Accessories: Includes mains power cable, user manual (digital format), and one GTL-16E probe per input channel</p>	1
19	Power supply	Branded Company Product with at least three years product warranty	<p>Output Configuration: 4-channel design with independent electrical isolation across all outputs</p> <p>Channel Output Ranges:</p>	1



			<ul style="list-style-type: none"> <li>CH1 &amp; CH2: Adjustable output voltage from 0 to 32V with a current delivery capacity up to 3A</li> <li>CH3: Variable range 0 to 5V supporting up to 1A</li> <li>CH4: Output adjustable from 0 to 15V with a load current of up to 1A</li> </ul> <p>Constant Voltage Operating Mode  Line Regulation: <math>\leq 0.01\% + 3 \text{ mV}</math>  (approximate value within rated voltage range)  Load Regulation: <math>\leq 0.01\% + 3 \text{ mV}</math> (across rated load variation)  Ripple &amp; Noise: <math>\leq 1 \text{ mVrms}</math> across full bandwidth</p> <p>Constant Current Operating Mode  Line Regulation: <math>\leq 0.2\% + 3 \text{ mA}</math>  Load Regulation: <math>\leq 0.2\% + 3 \text{ mA}</math>  Ripple Current: <math>\leq 3 \text{ mA rms}</math> (typical)  Safety &amp; Operational Features  Output Control: Independent output ON/OFF switching functionality is required  Voltage Resolution: Approximately 100 mV (*1)  Current Resolution: Approximately 10 mA (*1)</p> <p>Display Parameters  Display Units: Four separate displays required for individual channel status visualization  Display Type: 4.3-inch LCD (color or monochrome as applicable)</p> <p>Functional Features  Tracking Operation: Supported (required for synchronizing output behavior)  Auto Series/Parallel: Supported (automatic internal reconfiguration required)</p> <p>Power Requirements  Supply Input: 230V AC <math>\pm 10\%</math>, 50 Hz</p> <p>Mechanical Specifications  Maximum Dimensions (W x H x D): Within 200 mm x 100 mm x 200 mm  Maximum Weight: 10 kg or less</p>	
20	Function Generator	Branded Company Product with at least three years product warranty	Output Function: The equipment shall provide output waveforms including sine, square, triangle, and TTL signals as required. Frequency Range: For sine and square waveforms: approximately 0.1 Hz up to 3 MHz. For triangle waveform: approximately 0.1 Hz up to 1 MHz.	1




			<p>Frequency Resolution: Frequency resolution shall be maintained within a maximum of 0.1 Hz.</p> <p>Frequency Stability: The frequency stability shall be within <math>\pm 20</math> ppm (parts per million).</p> <p>Frequency Accuracy: The frequency accuracy shall be maintained within <math>\pm 20</math> ppm.</p> <p>Frequency Aging: Frequency aging shall not exceed <math>\pm 5</math> ppm per annum.</p> <p>Amplitude Range: Output amplitude shall be up to 10 V peak-to-peak (Vp-p) into a <math>50 \Omega</math> load.</p> <p>Amplitude Accuracy: Amplitude accuracy shall be within <math>\pm 20\%</math> at maximum amplitude setting.</p> <p>Output Impedance: Nominal output impedance shall be <math>50 \Omega</math> with a tolerance of <math>\pm 10\%</math>.</p> <p>Attenuator: A single-step attenuator of -40 dB <math>\pm 1</math> dB shall be provided.</p> <p>Display: A 6-digit LED display shall be incorporated for parameter indication.</p> <p>Output Control: Output shall be controlled via an ON/OFF selector switch.</p> <p>Power Source: The device shall operate on an AC supply of 240 V, 220 V, or 110 V <math>\pm 10\%</math>, with frequency 50/60 Hz.</p> <p>Ambient Operating Temperature: Normal operation shall be ensured within the ambient temperature range of 0 °C to 40 °C.</p> <p>Dimensions: Maximum dimensions shall not exceed 255 mm (W) <math>\times</math> 95 mm (H) <math>\times</math> 295 mm (D).</p> <p>Weight: Maximum device weight shall be within 2.5 kg.</p>	
21	Bench Top Multimeter	Branded Company Product with at least three years product warranty	<p>DC Voltage: Range: 500 mV to 1000 V across 5 ranges. Accuracy: <math>\pm(0.03\% \text{ rdg} + 4 \text{ digits})</math>.</p> <p>Input impedance: <math>10 \text{ M}\Omega</math>.</p> <p>AC Voltage (True RMS): Range: 500 mV to 1000 V across 5 ranges. Accuracy: <math>\pm(0.5\% - 5\% \text{ rdg} + \text{ digits})</math> depending on frequency and range.</p> <p>Input impedance: <math>10 \text{ M}\Omega</math>.</p> <p>DC Current: Range: 500 <math>\mu\text{A}</math> to 20 A across 6 ranges. Accuracy: <math>\pm(0.02\% - 0.3\% \text{ rdg} + 2 \text{ digits})</math> depending on range.</p> <p>AC Current (True RMS): Range: 500 <math>\mu\text{A}</math> to 20 A across 6 ranges. Accuracy: <math>\pm(0.5\% - 1\% \text{ rdg} + \text{ digits})</math> depending on frequency.</p> <p>Resistance: Range: 500 <math>\Omega</math> to <math>20 \text{ M}\Omega</math> across 6 ranges. Accuracy: <math>\pm(0.1\% - 0.3\% \text{ rdg} + \text{ digits})</math> depending on range.</p> <p>Diode Test: Max forward voltage 1.5 V, open voltage 2.8 V.</p> <p>Capacitance: Range: 5 nF to 50 <math>\mu\text{F}</math>. Accuracy: <math>\pm(2\% \text{ rdg} + 4 \text{ digits})</math>.</p>	1




			Frequency: Input level varies by range; functions include Auto/Manual Range, Max, Min, dBm, Rel, Hold. Continuity Beep: Threshold $<5\ \Omega$ . Display: Dual 7-segment LED, 0.4" and 0.5". Power Source: AC 100/120/230 V $\pm 10\%$ , 50/60 Hz. Dimensions & Weight: Approximately 251 x 91 x 291 mm; 2.6 kg.	
22	Non-Contact Voltage Tester	Branded Company Product with at least three years product warranty	Function: Non-contact AC voltage detection tester. Voltage Detection Range: Approximately 90 V to 1000 V AC. Detection Method: Capacitive, with visual and audible indication. Sensitivity: Adjustable sensitivity for different voltage ranges. Response Time: Instantaneous detection within standard operating conditions. Indicators: Bright LED indicators and audible beep for voltage presence. Operating Environment: Suitable for use in ambient temperatures from 0 °C to 40 °C. Power Source: Powered by standard batteries (typically 2 x AAA or equivalent). Safety Standards: Complies with IEC/EN 61010-1 CAT III 1000 V safety standards. Dimensions: Compact, handheld design suitable for field use (approx. 150 mm x 30 mm x 25 mm). Weight: Lightweight, approximately 150 g for ease of portability.	5
23	LCR Meter	Branded Company Product with at least three years product warranty	Display: Approximately 2.8" TFT touch LCD screen. Resolution: 25,000 or above counts resolution on both primary and secondary displays. Basic Accuracy: Within $\pm 0.2\%$ under standard conditions. Test Frequencies: Six or eight selectable frequencies depending on model variant. Measurement Combinations: Up to 15 different measurement combinations available. Test Level: Selectable AC test levels approximately 0.3 V, 0.7 V, and 1 V rms; DC test level selectable at $\pm 1\ V$ . Measurement Speed: Selectable measurement speeds of approximately 10 measurements per second (fast) and 2.5 measurements per second (slow). Auto LCR Mode: Automatic identification and measurement of component types within supported ranges. Data Hold: Feature available to hold measured data on display.	1

			Interface: USB virtual COM port provided for remote communication capabilities. Software: Datalogging software available for data capture and analysis.	
24	Soldering Station	Branded Company Product with at least three years product warranty	<p>Power Rating: Approximately 60 W maximum output power.</p> <p>Temperature Range: Adjustable from approximately 200 °C up to 480 °C.</p> <p>Temperature Stability: Within ±2 °C under normal operating conditions.</p> <p>Heating Element: Ceramic heating element for rapid heat-up and efficient temperature maintenance.</p> <p>Display: Digital or analog temperature display (depending on variant) for precise temperature control.</p> <p>Temperature Control: Adjustable via knob or digital interface with fine resolution.</p> <p>Power Supply: AC 220 V ±10%, 50/60 Hz.</p> <p>Features: Thermal cutoff and overload protection within required standards.</p> <p>Dimensions: Compact design with 100 mm × 100 mm × 90 mm (W × H × D) or above</p> <p>Weight: Approximately 1.5 kg for ease of portability and bench use.</p>	3
25	Digital Microscope	Branded Company Product with at least three years product warranty	<p>Specification: Magnification: 1600X</p> <p>Light source: 8 LED lights</p> <p>Resolution: 1920×1080, 640*480</p> <p>Pixel: 30W</p> <p>Focal length: 3-40mm manual adjustment</p> <p>Support Android 4.2 or above/widows/Mac system</p>	1
26	Soldering Rework Station	Branded Company Product with at least three years product warranty	<p>Soldering Iron Power: Up to approximately 60 W output power with temperature adjustable within approximately 200 °C to 480 °C range.</p> <p>Heating Element: Needle bit with MCH heater providing rapid heat-up and stable temperature control within ±2 °C.</p> <p>Hot Air Blower Power: Up to approximately 500 W output power with temperature adjustable within approximately 200 °C to 450 °C range, multiple nozzles included.</p> <p>Hot Air Features: Auto-pause function on placement in cradle, airflow adjustable within operational limits.</p> <p>DC Power Supply: Provides output voltage approximately 15 V up to 2 A maximum current plus 5 V USB output for auxiliary power.</p> <p>Control: Microcontroller-based system with LED indicators for temperature and mode selection.</p> <p>Safety: ESD-safe design compliant with applicable standards.</p>	1


			Build: Metallic body with powder coating, approximate dimensions 280 mm × 180 mm × 140 mm (W × H × D). Weight: Approximately 3.5 kg. Power Source: AC 220 V ±10%, 50/60 Hz. Accessories: Includes soldering iron with needle bit, hot air blower with 3 nozzles, iron stand with sponge, hot air cradle, patch cord, and power cord. Operating Temperature: Suitable for ambient temperature approximately 0 °C to 40 °C	
27	Hand Drill Machine	Branded Company Product with at least three years product warranty	Rated Input Power: Approximately 500 W or above maximum power consumption. Bit Holder: Standard 1/2"-20 UNF thread type. No-Load Speed (1st Gear): Adjustable from 0 up to approximately 3,000 rpm. Power Output: Approximately 300 W continuous output power. Weight: Approximately 1.7 kg total device weight. Impact Rate at No-Load Speed: Variable from 0 up to approximately 48,000 bpm. Rated Torque: Approximately 1.4 Nm maximum torque output. Drill Spindle Connecting Thread: Standard 1/2"-20 UNF thread. Chuck Capacity (Min/Max): Approximately 1.5 mm minimum to 13 mm maximum.	2
28	Cordless drill	Branded Company Product with at least three years product warranty	Torque (soft/hard/max.): Min 21/50/- Nm No-load speed (1st gear / 2nd gear): Min 0 – 500 / 0 – 1,900 rpm Weight incl. battery: 1.3 kg or less Max, impact rate: 27,000 bpm Battery type: Lithium-Ion or equivalent Chuck capacity, min./max.: 1.5 / 13 mm Weight excl. battery: 0.99 kg Torque settings: 20+2 or better	2
29	Jig Saw	Branded Company Product with at least three years product warranty	Rated Input Power: Approximately 500 W maximum power consumption. Voltage, Electrical: Nominal 230 V AC supply. Saw Stroke Length: Approximately 20 mm stroke length. Stroke Rate at No Load: Adjustable within approximately 800 to 3,100 spm (strokes per minute). Weight: Approximately 2.08 kg total weight. Bevel Angle: Adjustable within approximately - 45° to 45° range.	1
30	Miter Saw	Branded Company Product with at least three years product warranty	Rated Input Power: Approximately 1,750 W maximum power consumption. Saw Blade Diameter: Approximately 254 mm nominal diameter. Mitre Setting: Adjustable up to approximately 47° left and 52° right.	1




		years product warranty	Bevel Setting: Adjustable up to approximately 45° left and 0° right. Saw Blade Bore Diameter: Approximately 25.4 mm standard bore. Cutting Capacity at 0°: Approximately 90 mm x 130 mm maximum cross-section. Cutting Capacity at 45° Mitre: Approximately 90 mm x 91 mm maximum cross-section. Cutting Capacity at 45° Bevel: Approximately 60 mm x 130 mm maximum cross-section. Tool Dimensions (WxLxH): Approximately 477 mm x 559 mm x 567 mm. No-Load Speed: Fixed at approximately 5,000 rpm. Weight: Approximately 11.1 kg.	
31	Hot air gun	Branded Company Product with at least three years product warranty	Rated Input Power: Approximately 1,800 W maximum power consumption. Voltage, Electrical: Nominal 230 V AC supply. Weight: Approximately 0.75 kg. Working Temperature Range: Adjustable within approximately 60 °C to 550 °C. Heat-Up Time: Approximately 1 second to reach target temperature. Airflow: Adjustable within approximately 350 to 550 liters per minute. Airflow Control: Three selectable airflow settings.	2
32	Table saw	Branded Company Product with at least three years product warranty	Rated input power: Max 1800 W Incline setting: 45 ° L / 0 ° R Table size: Up to 555 x 555 mm Saw blade diameter: 254 mm Cutting height 90°: 80 mm Cutting height 45°: 55 mm Saw blade bore diameter: 30 mm Weight 24.4 kg or less Max. cutting capacity on the right: 545 mm No-load speed: 4300 rpm Cutting height 90°: 80 mm Cutting height 45°: 55 mm	1
33	Bench grinder	Branded Company Product with at least three years product warranty	Grinding wheel diameter: min 150 mm Rated input power: 350 W or more Grinding wheel widths: 20 mm or more No-load speed: upto 3,000 rpm Grinding wheel bore: 20 mm/2cm Grit 24, 60 or more Weight: 10 kg or less	1
34	Angle Grinder	Branded Company Product with at least three years product warranty	Rated Input Power: Approximately 670 W maximum power consumption. No-Load Speed: Approximately 11,000 rpm. Disc Diameter: Approximately 100 mm nominal diameter. Grinding Spindle Thread: Standard M10 thread. Weight: Approximately 1.5 kg.	1





			Switch: Lockable switch for operational safety.	
35	Straight Grinder	Branded Company Product with at least three years product warranty	Rated Input Power: Max 300 W power consumption. No-Load Speed: Up to 28,000 rpm. Voltage, Electrical: Nominal 230 V AC supply. Spindle Collar Diameter: Approximately 41 mm. Weight: Around 1.4 kg. Maximum Grinding Tool Diameter: Up to 25 mm. Maximum Collet Diameter: Up to 8 mm. Switch: Lockable switch for enhanced safety.	1
36	Circular Saw	Branded Company Product with at least three years product warranty	Rated Input Power: Approximately 1,400 W maximum consumption. Saw Blade Diameter: Nominal 184 mm diameter. Saw Blade Bore Diameter: About 20 mm standard bore size. Guide Rail Compatibility: Not compatible with guide rails. No-Load Speed: Typically 5,200 rpm. Weight: Around 4.1 kg	1
37	Blower	Branded Company Product with at least three years product warranty	Rated Input Power: Max 650 W power consumption. Weight: Approximately 1.7 kg. Voltage, Electrical: Nominal 230 V AC supply. Sound Pressure Level: Around 103 dB(A). Sound Power Level: Approximately 95 dB(A). Uncertainty (K): Within $\pm 3$ dB	1
38	Cordless Screw Driver	Branded Company Product with at least three years product warranty	Battery Capacity: Around 1.5 Ah nominal capacity. Torque (Soft/Hard/Max): Approximately 14 Nm / 30 Nm / Maximum not specified. No-Load Speed (1st Gear / 2nd Gear): Ranges from 0 up to 400 rpm and 0 up to 1,500 rpm respectively. Battery Type: Rechargeable Lithium-Ion battery. Chuck Capacity (Min/Max): From approximately 0.8 mm up to 10 mm. Weight (Excluding Battery): About 0.8 kg. Torque Settings: 20 plus 1 adjustable settings.	1
39	Vacuum Cleaner	Branded Company Product with at least three years product warranty	Rated Input Power: Approximately 1,100 W maximum power consumption. Weight: Around 6 kg total weight. Container Volume (Net): Approximately 10 liters capacity. Voltage, Electrical: Nominal 230 V AC supply. Container Volume (Gross): Approximately 15 liters total volume. Container Volume (Net, Water): About 8 liters capacity for water. Filter Surface Area: Around 2,300 cm <sup>2</sup> effective filtration area. Airflow Rate (Turbine): Approximately 53 liters per second.	1



			Vacuum Pressure (Turbine): Up to 270 mbar vacuum pressure. Number of Wheels: Four wheels for mobility.	
40	Random orbit sander	Branded Company Product with at least three years product warranty	Rated Input Power: Up to 280 W maximum consumption. Sanding Pad Diameter: Nominal 125 mm diameter. Orbit Diameter: Approximately 2.6 mm orbital diameter. Weight: Around 1.4 kg. No-Load Speed: Adjustable within 7,500 to 12,000 rpm range. Orbital Stroke Rate: Between 15,000 and 24,000 orbits per minute (opm). Eccentricity: Approximately 1.3 mm.	1
41	Planer	Branded Company Product with at least three years product warranty	Rated Input Power: Not exceeding 710 W under nominal operating conditions. Planing Width: Approximately 82 mm effective width capacity. Planing Depth: Within the range of up to 2.6 mm maximum depth per pass. Weight: Circa 2.8 kg total unit mass. Adjustable Rebating Depth: Maximum adjustable depth of approximately 9 mm, No-Load Speed: Operating speed typically around 18,000 rpm.	1
42	Cordless Vacuum Cleaner with Starter kit	Branded Company Product with at least three years product warranty	Battery Voltage: Rated at approximately 18.0 V nominal voltage. Weight Excluding Battery: Around 1.3 kg without battery attached. Container Volume: Approximately 0.7 liters net capacity. Filter Surface Area: Roughly 55 cm <sup>2</sup> filtration surface. Maximum Airflow Rate (Turbine): Up to 10 liters per second. Maximum Vacuum Pressure (Turbine): Not exceeding 60 mbar under standard conditions. Operating Time (18 V Battery): Typically 7 minutes per Ah of battery capacity.	1
43	Rotary Tool Kit	Branded Company Product with at least three years product warranty	Rated Power Input: Approximately 175 W within nominal voltage range. Voltage: Operates within 220 to 240 V AC supply. Weight: Around 0.66 kg total mass. Length: Approximately 24 cm overall length. Width: About 4.1 cm nominal width. Depth: Roughly 4.3 cm depth dimension. No-Load Speed: Variable speed ranging from 5,000 up to 35,000 rpm. Battery Technology: Not applicable (n.a.). Speed Setting: Fully variable speed control as required. Accessory Quick Change System: Equipped with multi chuck for rapid accessory interchange. Vibration Level: Approximately 18 m/s <sup>2</sup> measured vibration	2




44	Rubber Grip Hacksaw	Very Good Quality	Depth of Throat: Approximately 98 mm (3.85 inches) nominal depth. Blade Length: Around 254 mm (10 inches) standard length.	2
45	Hacksaw Mini	Very Good Quality	Blade Length: Approximately 10 inches nominal length. Handle Material: Constructed from metal as standard. Overall Length: Around 11 inches total length.	2
46	Claw Hammer Steel Shaft	Very Good Quality	Weight: Approximately 8 oz (220 grams) nominal weight. Dimensions: Around 27.8 cm x 12.4 cm x 3.6 cm (L x W x H) overall size	2
47	Ball Pein Hammer	Very Good Quality	Weight: Approximately 110 grams nominal weight. Dimensions: Around 32.6 cm x 10 cm x 2 cm (L x W x H) overall measurements.	2
48	Rubber mallet	Very Good Quality	Weight: Approximately 450 grams nominal weight. Dimensions: Around 33.6 cm x 9.6 cm x 6.2 cm (L x W x H) overall size.	2
49	Ring spanner set 12Pcs	Very Good Quality	Weight: 3.08 Kg nominal weight. Quantity: 12 pcs per set. Size: 6 mm to 32 mm overall range.	1
50	Open end spanner set 12Pcs	Very Good Quality	Weight: Approx1.74Kg nom.wt. Qty: 12pcs/set. Size: 6mm-32mm overall dims.	1
51	Combination Spanner set 8Pcs	Very Good Quality	Weight: Approx649g nom.wt. Qty: 8pcs/set.	1
52	Allen key set 10pcs	Very Good Quality	Hex Key Size: 1.5,2,2.5,3,4,5,5.5,6,8,10mm; Qty:10pcs/set	2
53	Allen key set 12pcs	Very Good Quality	BallKeySize:1/16",5/64",3/32",7/64",1/8",9/64",>5/32",3/16",7/32",1/4",5/16",3/8" Qty:12pcs/set	2
54	Combination plier	Very Good Quality	Weight: Approx422g nom.wt. Size: 8"/200mm nominal	2
55	Long nose plier	Very Good Quality	Weight: Approx399g nom.wt. Size:180mm/6" nominal	2
56	Circlip straight 5"	Very Good Quality	Weight: Approx399g nom.wt. Size:130mm/5" nominal	2
57	Circlip bent	Very Good Quality	"Weight: Approx399g nom.wt. Size:130mm/5" nominal"	2
58	Diagonal Cutter	Very Good Quality	"Weight: Approx239g nom.wt. Size:180mm nominal"	2
59	Wire Stripper	Very Good Quality	Weight: Approx281g nom.wt. Size:130mm nominal	2
60	Adjustable spanner	Very Good Quality	Size: Upto 150 mm	2
61	Pipe wrench	Very Good Quality	Size: Max 300 mm	2
62	C - clamp	Very Good Quality	Size: Upto 75 mm	4
63	C-clamp	Very Good Quality	Size: Upto 150 mm	4




64	Snap- off Knife	Very Good Quality	Size:18 mm	2
65	16pcs screw driver set	Very Good Quality	Pieces Per Set: 16 pcs	1
66	6pcs precision screw driver set	Very Good Quality	Pieces Per Set: 16 pcs	2
67	Max steel snip cutter	Very Good Quality	Length: 250 mm	2
68	PVC Pipe cutter	Very Good Quality	Length: 42 mm	2
69	Hot Glue Gun	Very Good Quality	Power: 40 W	4
70	Small file set	Very Good Quality	Length: 160 mm	2
71	Big file set	Very Good Quality	Length: 200 mm	2
72	Chisel set	Very Good Quality	Weight: 340 gm	2
73	Punch set	Very Good Quality	Weight: 390 gm	2
74	Bench wise	Very Good Quality	Base Type: Fixed Size:2-3½" nominal JawWidth:60mm	2
75	Router Bit Starter Kit	Very Good Quality	Pieces Per Set: 15 pcs	1
76	Drill bit set	Very Good Quality	WAF(mm):1,1.5,2,2.5,3,3.5,4,4.5,5,5.5,6,6.5,7,7.5,8,8.5,9,9.5,10,10.5,11,11.5,12,12.5,13 Wt:~1.3Kg nom.wt Sz(mm):205×115×55 overall	2
77	Baby wise	Very Good Quality	Vice Type: Bench Size:2" nominal JawWidth:50mm	2
78	Ratchet Set	Very Good Quality	Vice Type: Bench Sz:2" nominal; Jaw:50mm	2
79	Pegboard	Very Good Quality		5
80	Digital Vernier Caliper	Very Good Quality	Product Type: Digital Calliper Meas.Range:0-150mm / 0-6" Resolution:0.01mm	2
81	Micrometer	Very Good Quality	Resolution:0.001mm/0.00005" Meas.Range:0-25mm/0-1"	1
82	Steel Rule 300mm	Very Good Quality	Product Type: Steel Rule ScaleSize:12"/300mm Material: Stainless Steel	5
83	Steel Rule 600mm	Very Good Quality	Product Type: Steel Rule ScaleSize:24"/600mm Material: Stainless Steel	5
84	Engineering Square	Very Good Quality	Size:150×80mm nominal Material: Carbon Steel	2
85	Meter Tape 30m	Very Good Quality	Length: 30 m	1
86	Measuring Tape 3M	Very Good Quality	Length: 3 m	3
87	Measuring Tape 5M	Very Good Quality	Length: 5 m	3
88	Spirit Level	Very Good Quality	Vials:3 Accuracy:0.5mm/m Length:300mm Product Type: Level	3
89	Goggle	Very Good Quality	Goggle - Industrial Standard Make	5



90	Apron	Very Good Quality	Apron - Standard Make	5
91	Ear Muff	Very Good Quality	Earmuff - Industrial Standard Make	5
92	Mask	Very Good Quality	Mask - Industrial Standard Make	50
93	Fire Extinguisher	Very Good Quality	Fire Extinguisher- Industrial Standard Make	6
94	First Aid Kit	Very Good Quality	First Aid Kit – Industrial Standard Make	2
95	Gloves Pair	Very Good Quality	Gloves – Industrial Standard Make	10
96	Normal Oven	Branded Company Product with at least three years product warranty	Oven Cap: 20L or more Type: Solo Door: Side Swing Child Lock: Yes Completion Beeper: Yes Power Levels: upto 5 Control: Membrane Type Cavity Mat: Anti-Bacterial Dims(mm):455×252×320 PowerOut:700W or less	1
97	Refrigerator	Branded Company Product with at least three years product warranty	Capacity:183L or more AnnualEnergyConsumption:148kWh/Year or less RefrigeratorFreshFoodCapacity:165L or more Freezer Capacity: min 18L BottleCount:5 or more NoiseLevel:40dB or less Installation Type: Freestanding	1
98	Smart Board	Branded Company Product with at least three years product warranty	Display Size: Approx 75Inch (190 cm) Up to Resolution: 4KUHD or Higher Brightness: Min 350 nits; Typ 400 nits Approx Contrast Ratio: Typ 1200: 1 Upto Response Time: Approx 8ms Viewing Angle: Approx 178 Degrees Wide Working Frequency: 1.5GHz Nominal RAM: 4GB Or More Internal Storage: 32GB Min OS: Android Based HDMI: 3 Ports USB: 2 Ports Sensing Type: Infrared Touch Frame Surface Protection: 4mm Toughened Glass Or Equivalent Infrared Touch Points: 20 Approx Voltage: DC+5V±5% Range OPS: Optional	1
99	Projector	Branded Company Product with at least three years product warranty	Projection Tech: RGB liquid crystal shutter projection (3LCD) Up to Connectivity: USB Type B: 1 port (Firmware Update/Copy OSD) Approx Analog Input: D-Sub 15 pin: 1 port Digital Input: HDMI: 1 port Projection Lens: Type: No Optical Zoom/Focus (Manual) Nominal	1




			FocalLength:16.70mm Approx FNumber:1.44 Nominal Zoom:1.44-1.95 Ratio (Wide to Tele) ThrowRatioRange:1.00-1.35(Digital Zoom Approx)	
100	Printer	Branded Company Product with at least three years product warranty	Functions: Print, Scan, Copy Printer Type: Laser Nominal Dims(mm):409×398.5×267Approx Weight:9.7KgNominal PrintSpeed:Upto30ppm(A4Size)Approx Warranty:1YearOn-Site PrintResolution:600×600dpi,HQ1200(2400×600dpi) Quality Approx 2Sided-Duplex- PaperType:Plain,Thin,RecycledApprox 2Sided-Duplex-PaperSize:A4 PaperHandling:Tray#1- PaperType:Plain,Thin,Recycled Tray#1- MaxCapacity:Upto250Sheets(80g/m <sup>2</sup> )Approx PaperOutput:Upto100Sheets(80g/m <sup>2</sup> )FaceDownTray;OneSheetFaceUpTrayApprox Copy- Colour /Mono: Yes/Yes Multiple Copies: Sorts/StacksUpto99PagesApprox Enlarge/Reduce:25%400%(In1%Steps)Approx CopyResolution:600×600dpi 2Sided-Duplex- CopyPaperType:Plain,Thin,Recycled 2Sided-Duplex-CopyPaperSize:A4 Scan- ResolutionInterpolated:Upto19200×19200dpiApprox Scan- ResolutionGlass:Upto600×2400dpiApprox Connectivity:Hi-SpeedUSB2.0 DisplayType:16Chars×2Lines MemoryCapacity:32MBApprox PowerSource:220-240VAC50/60Hz PowerConsumption-Ready:Approx60W PowerConsumption-Sleep:Approx6.6W PowerConsumption-Off:Approx0.08W NoiseLevel:50dB(A)Approx	1
101	Desktop	Branded Company Product with at least three years product warranty	CPU: INTEL CORE I7-12THGEN or Higher RAM:8GB+512GB SSD or more Conn: LAN+WIFI+BLUETOOTH+KEYMOUSE Display:20" DESKTOP MONITOR	5
102	3D printer Filament	Very Good Quality	Weight Kg: 1 Approx Melt Flow Index: 2 (190°C/2.16kg) Nominal FilamentLength:330mApprox	10




			Dim Accuracy: +/-0.1mmApprox Roundness Accuracy: +/-0.5mmApprox SpoolInnerDia:55mmNominal SpoolOuterDia:200mmApprox SpoolWeight:300gNominal SpoolWidth:65mmApprox	
103	Acrylic Sheet 3mm, 4ft x 4ft	Very Good Quality		20
104	Acrylic Sheet 4mm, 4ft x 4ft	Very Good Quality		20
105	Acrylic Sheet 5mm, 4ft x 4ft	Very Good Quality		20
106	Foam Sheet 8mm, 4ft x 4ft	Very Good Quality		2
107	Foam Sheet 10mm, 4ft x 4ft	Very Good Quality		1
108	Foam Sheet 12mm, 4ft x 4ft	Very Good Quality		1
109	Foam Sheet 15mm, 4ft x 4ft	Very Good Quality		1
110	Ply Board 5mm, 2ft x 4ft	Very Good Quality		12
111	Nylon Rod 10mm, 1m	Very Good Quality		5
112	Nuts (3mm,4mm,5mm, 6mm,8mm,10mm, 12mm) Pack of 100	Very Good Quality		1
113	Bolts (3mm,4mm,5mm, 6mm,8mm,10mm, 12mm) dia 1" Inch Pack of 100	Very Good Quality		1
114	Screws (3mm,4mm,5mm) Pack of 100	Very Good Quality		1
115	Washers (3mm,4mm,5mm, 6mm,8mm,10mm, 12mm) Pack of 100	Very Good Quality		1
116	Studs (6mm,8mm) 1 Meter	Very Good Quality		2
117	Nails (1",2",3",1.5",5") Pack of 100	Very Good Quality		1
118	Fevicol 2Kg	Very Good Quality		1
119	2 Way Tape	Very Good Quality		10



120	PVC Pipe .75",10ft	Very Good Quality		10
121	PVC Pipe 1",10ft	Very Good Quality		10
122	PVC Pipe 1.5",10ft	Very Good Quality		10
123	PVC Pipe 2.0",10ft	Very Good Quality		10
124	Aluminium channels (L, C, Box, strip length 12ft)	Very Good Quality		2
125	PCB Drill Bit 0.4mm	Very Good Quality		10
126	PCB Drill Bit 0.8mm	Very Good Quality		10
127	PCB Drill Bit 1mm	Very Good Quality		10
128	Drill Bit 4mm	Very Good Quality		10
129	Drill Bit 5mm	Very Good Quality		10
130	Drill Bit 6mm	Very Good Quality		10
131	Arduino UNO R3	Very Good Quality		10
132	Arduino NANO	Very Good Quality		10
133	Arduino Mega	Very Good Quality		10
134	Raspberry Pi Model 4B, 4GB	Very Good Quality		10
135	ESP8266 NodeMCU	Very Good Quality		10
136	ESP32 Development Board	Very Good Quality		10
137	Beaglebone blu	Very Good Quality		5
138	Beaglebone Black	Very Good Quality		5
139	Voltage Regulator Module	Very Good Quality		10
140	Mini Micro submersible Water Pump	Very Good Quality		10
141	Piezoelectric Plate	Very Good Quality		10
142	8*8 LED Matrix Module	Very Good Quality		10
143	Bluetooth	Very Good Quality		10
144	7 Segment LED Display	Very Good Quality		10
145	GSM/GPRS/GPS Module	Very Good Quality		10
146	Laser Module	Very Good Quality		10
147	LDR Module	Very Good Quality		10
148	4x4 Matrix Keypad	Very Good Quality		10
149	Joy Stick Module	Very Good Quality		10



150	Active Buzzer (BIG)	Very Good Quality		10
151	Active Buzzer (SMALL)	Very Good Quality		10
152	Motor Driver	Very Good Quality		10
153	Sound Playback Module	Very Good Quality		10
154	BO Motors	Very Good Quality		20
155	Vibrating Motor	Very Good Quality		10
156	Capacitive Touch Switch	Very Good Quality		10
157	IR Sensors (Obstacle Sensors)	Very Good Quality		10
158	Triple Axis Magnetometer	Very Good Quality		10
159	Humidity Sensor	Very Good Quality		10
160	MQ-2	Very Good Quality		10
161	MQ-3	Very Good Quality		10
162	MQ-4	Very Good Quality		10
163	MQ-5	Very Good Quality		10
164	MQ-7	Very Good Quality		10
165	Ultrasonic Sensor Module	Very Good Quality		10
166	Triple Axis accelerometer	Very Good Quality		10
167	PIR Motion Detector Module	Very Good Quality		10
168	Pulse Rate Heart Sensor	Very Good Quality		10
169	Relay Module	Very Good Quality		10
170	Soil Moisture Sensor	Very Good Quality		10
171	Touch Sensor	Very Good Quality		10
172	Rain Drop Sensor	Very Good Quality		10
173	Flex Sensor	Very Good Quality		10
174	Temperature Sensor	Very Good Quality		10
175	Force Pressure Sensor	Very Good Quality		10
176	Colour Recognition Sensor	Very Good Quality		10
177	Water Flow Sensor	Very Good Quality		10
178	Sound Sensor	Very Good Quality		10
179	IR Sensor Array for Line Following	Very Good Quality		10



180	RFID Reader-Tags	Very Good Quality		10
181	RF Modules Tx& Rx 315 MHz ASK	Very Good Quality		10
182	Stepper motor with Driver Board	Very Good Quality		10
183	Servo Motor 360 rotation	Very Good Quality		10
184	Servo Motor 180 rotation	Very Good Quality		10
185	Metal Gear Servo Motor (180° Rotation)	Very Good Quality		10
186	Solder Wire 100grm	Very Good Quality		10
187	Solder Flux	Very Good Quality		10
188	830 Points Solderless Breadboard	Very Good Quality		10
189	400 Points Solderless Breadboard	Very Good Quality		10
190	Copper Clad Board single side	Very Good Quality		50
191	Copper clad board double side	Very Good Quality		50
192	Male to Male Breadboard Jumper	Very Good Quality		200
193	Female to Female Breadboard Jumper	Very Good Quality		200
194	Male to Female Breadboard Jumper	Very Good Quality		200


## Terms and Conditions

The following Terms and Conditions apply to all bidders participating in the tender for the supply, installation, and commissioning of equipment, tools, and machines for the establishment of an AICTE IDEA Lab. All prospective vendors are required to read and comply with these terms in their entirety.

### 1. General Information

All equipment and materials must be delivered in the quantities and specifications as mentioned in the purchase order issued by the purchaser. The delivery location will be specified in the purchase order (e.g., XYZ Institute of Technology, [Insert Address]). The entire contract shall remain valid for a period of three (3) months from the date of award.

Quotations submitted by bidders must remain valid for a minimum of 90 days from the final date of submission. Any quotation that does not meet this validity period will be considered non-compliant.



## 2. Bid Submission Guidelines

Bids may be submitted either via email (digitally signed) or in hard copy form, as specifically mentioned in the tender notice. All quotations must be printed on the bidder's official letterhead and duly signed by an authorized representative.

Each bid must be complete in all respects and must include the following mandatory documents:

- Detailed Profile of the Bidder, highlighting experience and key competencies.
- Copy of the Company/Firm Registration Certificate.
- Copy of valid GST Registration Certificate.
- Copy of submitted GST return (at least up to November 2024).
- Copy of valid PAN Card.
- Chartered Accountant's Certificate for turnover for FY 2021–22, 2022–23, and 2023–24.
- CA-certified and audited Balance Sheets and Financial Statements (Form 3CB/3CA) for the last three financial years.
- Copies of Work Completion or Experience Certificates of similar completed works.
- Valid Shop Establishment License or Factory License.
- Genuine Manufacturer Authorization Form (MAF), which will be subject to verification with the respective OEM.
- Bidder should provide an Escalation Matrix for service and after sales support.
- Valid EPF, ESIC, and Professional Tax Registration Certificates (where applicable).
- Income Tax Return Acknowledgements for FY 2021–22, 2022–23, and 2023–24.
- Declaration/Affidavit (on ₹500/- Stamp Paper) regarding no blacklisting from IITs/NITs/Govt. Offices/PSUs/Autonomous Bodies.
- Complete, signed, and stamped tender document including amendments and deviation sheets, if any (to be uploaded online only).
- Declaration of agreed specifications on company letterhead, duly signed and stamped.
- Any other documents in support of technical eligibility.

All bidders are required to quote for all the items listed in the BoQ. Partial or item-wise quotations will be summarily rejected. Each bidder is allowed to submit only one quotation per package; multiple submissions from a single bidder will lead to disqualification.



### **3. Technical Documentation and Compliance**

The bidder must furnish complete technical documentation for each quoted item. This includes detailed product specifications, installation manuals, operation and maintenance manuals. The bidder is also required to submit a layout/design proposal aligned with the lab setup requirements, highlighting compliance points against the tender specifications.

Original technical brochures or scanned versions of product catalogues should be submitted with the bid. Wherever available, URLs to the OEM's official product page should also be provided for cross verification.

Each bidder must clearly mention the make, model, and complete technical specifications for the equipment being offered. A compliance sheet responding to each technical requirement outlined in the tender must be prepared and duly signed.

### **4. Eligibility and Qualification Criteria**

All bidders must be OEMs or authorized partners/distributors with valid authorization for the products they are quoting. Authorization letters must be submitted on the OEM's official letterhead.

Bidders must demonstrate relevant experience by submitting a minimum of three Purchase Orders (executed within the last five years) for similar equipment supplied to academic, R&D, or industrial institutions. A list of at least five institutional clients (with contact information) must be provided as a reference.

It is mandatory that the bidder or OEM has a registered support office in India to provide warranty and after-sales support. In the case of imported equipment, either the OEM or their authorized seller must submit a certificate confirming the presence of such a service support facility in India.

The OEM must also submit a declaration confirming the availability of spare parts for the quoted products for a minimum of one year and authorize the bidder to participate in the tender.

### **5. Financial Criteria**


Each bidder must have an average annual turnover of ₹5 Crores or more over the last three financial years (FY 2022–23, 2023–24, 2024–25). The turnover must be supported by a CA certificate or audited financial statements.

Prices quoted must be inclusive of all taxes (GST, customs, etc.), transportation, packaging, insurance, unloading, installation, commissioning, and training charges. There shall be no extra claim under any circumstances after the finalization of the bid.

The quoted prices must be firm and fixed throughout the duration of the contract. No escalation in price will be allowed under any pretext.

### **6. Evaluation and Award of Contract**

All bids will be evaluated on the basis of compliance with the technical specifications, completeness of submitted documentation, financial eligibility, and price competitiveness. The contract shall be awarded to the bidder whose offer is determined to be technically responsive and lowest in cost.



The purchaser reserves the absolute right to reject any or all bids without assigning any reason. The final decision on selection will be at the sole discretion of the purchaser and shall be binding on all parties.

## **7. Warranty and After-Sales Service**

All equipment must carry a minimum onsite warranty of at least **three years** from the date of successful installation and commissioning. During this warranty period, the bidder shall repair or replace any defective items at no additional cost to the purchaser. All associated transportation, testing, and labor costs shall be borne by the bidder.

In case of any service delay or failure to resolve issues during the warranty period, the purchaser reserves the right to invoke penalties or reject future business from the vendor.

## **8. Payment Terms**

Payment shall be released only after the successful supply, installation, and commissioning of the equipment. Final inspection and acceptance will be carried out by the purchaser's technical committee.

No payment shall be made for equipment that is received in damaged condition, is non-functional, or fails to meet the required specifications. The bidder must submit all necessary documentation (delivery challans, installation report, warranty documents, training certificate, invoice, etc.) to process payment.

## **9. Other Conditions**

No bidder shall be given preference based on category, class, or affiliation. The procurement may be extended to additional phases (e.g., Phase II) depending on availability of funds and institutional requirements.

Delayed delivery or installation may result in cancellation of order or imposition of penalties, as deemed fit by the purchaser. The scope of the supply and service must be entirely as per the BoQ and technical specifications. Bids with partial compliance or deviations shall not be entertained.

## **10. Submission Deadline and Contact Details**

All quotations must be submitted by **04-02-2026, 5:00 PM** to the email ID **principal@rgmcet.edu.in** or sent in hard copy to:

The Principal  
Rajeev Gandhi Memorial College of Engineering & Technology  
NH-40, Nerawada Cross Roads  
Nandyal – 518501

Contact: Dr B. Sidda Reddy, 9440844600 Email: bsrrgmcet@gmail.com

